Amendment Dated 2/23/2006 Reply to Office Action of 11/23/2005

In the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

- 1 (currently amended). A gathering and picking device for standing plants having useful parts comprising:
- a picking gap defined by a stripper plate, the picking gap [[having]] comprising an inlet portion for receiving standing plants and having a first side and a second side opposite the first side:
- a gathering element is arranged mounted for rotation on the first side of the picking gap and is rotated about a predominantly vertical axis, the gathering element is provided with elongated_carrier elements that are designed to grasp the standing plants as the gathering and picking device is being operated, the gathering element having a first operating envelope;
- a conveying element comprises a series of teeth radially projecting from a generally circular core to a lesser radial extent than the elongated carrier elements and cooperates with the gathering element to introduce the standing plants into the picking gap, the conveying element is arranged mounted for rotation on the second side of the picking gap upstream of the inlet portion of the picking gap, to convey the standing plants over at least part of the length of the picking gap, the conveying element is rotated about a predominantly vertical axis, the conveying element having a second operating envelope partially overlapping with the first operating envelope; and
- a picking unit is operated to convey the standing plants downward through the picking gap so the useful parts of the standing plants are separated from the standing plants by the stripper plate.
- 2 (canceled). The gathering and picking device as defined by claim 1 wherein the conveying element is provided with protruding teeth-like carrier elements.
- 3 (currently amended). The gathering and picking device as defined by claim [[2]] 1 wherein the carrier elements of the conveying element are distributed circumferentially over a disk.

John Deere

- 4 (original). The gathering and picking device as defined by claim 3 wherein pocket-like recesses are formed between the carrier elements of the conveying element.
- 5 (currently amended). The gathering and picking device as defined by claim 1 wherein the picking unit comprises at least one picking roll having a point, the point is arranged beneath the inlet portion of the picking gap.
- 6 (canceled). The gathering and picking device as defined by claim 1 wherein gathering element has an operating envelope and the conveying element has an operating envelopes of the gathering element and of the conveying element overlap.
- 7 (currently amended). The gathering and picking device as defined by claim 1 wherein the conveying <u>element</u> is rotated faster than the gathering element is rotated.
- 8 (currently amended). The gathering and picking device as defined by claim
 1 wherein the conveying <u>element</u> is rotated at approximately the same speed the
 gathering element is rotated.
- 9 (original). The gathering and picking device as defined by claim 1 wherein the conveying element is arranged above the picking gap.
- 10 (original). The gathering and picking device as defined by claim 1 wherein the conveying element is arranged below the picking gap.
- 11 (original). The gathering and picking device as defined by claim 1 wherein the conveying element is arranged above and below the picking gap.
- 12 (original). The gathering and picking device as defined by claim 1 wherein the conveying element is arranged beneath the gathering element.
- 13 (original). The gathering and picking device as defined by claim 1 wherein the conveying element is arranged above the gathering element.
- 14 (original). The gathering and picking device as defined by claim 1 wherein the conveying element is arranged above and beneath the gathering element.

Amendment Dated 2/23/2006 Reply to Office Action of 11/23/2005

15 (currently amended). The gathering and picking device as defined by claim 1 wherein the conveying element has an operating envelope, the second operating envelope of the conveying element terminates approximately at the inlet portion of the picking gap.

16 (previously presented). The gathering and picking device as defined by claim 1 wherein the teeth are generally triangular.

17 (previously presented). The gathering and picking device a defined by claim 1 wherein the teeth are generally triangular with rounded peaks.